



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO

TOLL FREE: 877-636-0500

www.LEGACYTRACTORS.COM

Specifications

CATEGORY	XG3032	XG3032H	XG3037	XG3037H
ENGINE				
Type	3-cylinder, indirect-injection, Water-cooled			
Model(Tier4)	N843T-F-24		N843T-F-27	
Engine HP(Gross)	32.2		36.2	
PTO HP	27.4	25.8	30.8	29
Rated speed, RPM	2,600			
Displacement-cu, in ³ .	91.3			
Fuel tank capacity(gal)	7.4			
Alternator(V-A)	12V - 85 Amps			
DRIVE TRAIN				
Transmission	Synchro Shuttle	HST	Synchro Shuttle	HST
No. of Speed	F12 x R12	3 Ranges	F12 x R12	3 Ranges
Brakes	Wet, Multi - disc			
Steering	Hydrostatic Power Steering			
PTO				
Type	Independent			
Rear(rpm)	Standard (540 rpm)			
HYDRAULIC SYSTEM				
Control system	Position			
Implement pump, gpm	8.2			
Steering pump, gpm	4.2	5.2	4.2	5.2
Total flow, gpm	12.4	13.4	12.4	13.4
Category, 3pt hitch	CAT I			
Hitch Lift capacity, lbs(Hitch end)	1,808			
Remote valves	Option			
DIMENSION				
Overall length, Bumper to link in.	123			
Overall width with tires, in.	55.5			
Wheelbase, in.	67.5			
Ht to top of rops, in.	89			
TIRE SIZE				
Ag Front / Rear	7 - 14 / 11.2 - 24			
IND Front / Rear	25 x 8.5 - 14 / 43 x 16 - 20			
Turf Front / Rear	25 x 8.5 - 14 / 41 x 14 - 20			
WEIGHT				
Total weight without ballast, lbs.	2,822	2,855	2,822	2,855

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Power steering
- Switch operated Independent rear PTO
- ROPS with seat belt
- Hydraulic position control
- Differential lock
- Draw bar
- Pre-heat starting aid
- Safety flashers
- Fuel, coolant temperature, tachometer & hour meter gauges
- Pre-heating, parking brake, battery charging, engine oil pressure, fuel filter, PTO operation and high beam operation/warning lights

Front end Loader	LL3108	LL3109
Tractor Application		
	XG3032 / XG3032H	XG3037 / XG3037H
Bucket, in.	66	66
Maximum Lift height, in.	93.7	93.7
Clearance with Attachment Dump, in.	62.4	62.4
Reach at Maximum Height, in.	13.2	13.2
Maximum Dump Angle, deg.	65	65
Maximum Rollback Angle, deg.	41	41
Digging Depth, in.	4.0	4.0
Overall Height in Carry Position, in.	48.9	48.9
Lift Capacity(@ Pivot pin), lbs.	1,612	2,088
Breakout Force(@ Pivot pin), lbs.	2,604	3,320
Approx. Weight (Loader w/o Bucket), lbs.	1,124	1,124

Backhoe	LB1105
Tractor Application	
	XG Series
Digging Depth, in.	76.3
Reach from centerline of swing Pivot, in.	113.1
Loading Height, in.	63.6
Swing Arc, deg.	180
Transport Height, in.	77.2
Bucket Rotating, deg.	180
Stabilizer Spread(Down position), in.	68.7
Stabilizer Spread(Up position), in.	46.4
Bucket Digging force, lbs.	2,817

