



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO
TOLL FREE: 877-636-0500
www.LEGACYTRACTORS.COM

Specification

	XJ 2025	XJ 2025H
ENGINE		
Type	3 - Cylinder, Indirect - injection, Water - cooled	
Model(Tier 4)	Mitsubishi S3L2	
Engine HP(gross)	24.4	
PTO HP	19.5	18.5
Rated speed(rpm)	2,500	
Displacement-cu(in ³)	80.4	
Fuel tank capacity(gal)	6.6	
Alternator(V-A)	12V - 50 Amps	
DRIVE TRAIN		
Transmission	Sliding Shift	Hydrostatic Drive
No. of Speed	6F x 2R	2 Ranges
Brakes	Wet, Multi - disc	
Steering	Hydrostatic Power Steering	
PTO		
Type	Electro Hydraulic Clutch PTO	Independent
Rear(rpm)	Standard (540 rpm)	
Mid(rpm)	Standard (2000 rpm)	
HYDRAULIC SYSTEM		
Implement pump(gpm)	6.9	5.9
Steering pump(gpm)	1.1	2.6
Total flow(gpm)	8.0	8.5
Category(3pt hitch)	CAT 1	
Hitch Lift capacity, lbs(Hitch end)	1,433	
Lift control type	Position	
DIMENSION		
Overall length(Bumper to link in)	103	
Overall width with tires(in)	44.9	
Wheelbase(in)	59	
Ht to top of rops(in)	92.3	
TIRE SIZE		
IND Front / Rear	23 x 8.5 - 12 / 33 x 12 - 16.5	
Turf Front / Rear	23 x 8.5 - 12 / 33 x 12.5 - 16.5	
WEIGHT		
Total weight without ballast(lbs)	1,785	1,609

Note Specifications and design are subject to change without prior notice.

- Power steering
- Switch operated Independent PTO, rear & mid (XJ 2025H)
- Lever selector for rear PTO, mid PTO or both (XJ 2025)
- Foldable ROPS
- Rear work light
- Hydraulic position control
- Differential lock
- Draw bar
- Pre-heat starting aid
- Safety flashers & turn signals
- Fuel, coolant temperature, tachometer & hour meter gauges
- Pre-heating, parking brake, battery charging, engine oil pressure, PTO operation and high beam operation/warning lights

Front End Loader	LL2101
Tractor Application	XJ 2000 Series
Maximum Lift height(in)	85.7
Clearance with Attachment Dump(in)	65
Reach at Maximum Height(in)	22
Maximum Dump Angle(deg)	52
Maximum Rollback Angle(deg)	43
Digging Depth(in)	4.4
Overall Height in Carry Position(in)	42.8
Lift Capacity(@ Pivot pin)(lbs)	1,277
Breakout Force(@ Pivot pin)(lbs)	1,643
Approx. Weight (Loader w/o Bucket)(lbs)	638

Backhoe	LB1104
Tractor Application	XJ 2000 Series
Digging Depth(in)	79.3
Reach from centerline of swing Pivot(in)	113.3
Loading Height(in)	56.9
Swing Arc(deg)	150
Transport Height(in)	75.2
Bucket Rotating(deg)	163
Stabilizer Spread(Down position)(in)	87.7
Stabilizer Spread(Up position)(in)	55.7
Bucket Digging force(lbs)	2,096

Mid-mount Mower	LM3560
Tractor Application	XJ 2000 Series
Cutting Width(in)	60
Overall Width(in)	74
Cutting Height Range(in)	1 to 4-1/8
Deck shell Thickness(in)	10-Gauge (0.1345 in.) Grade 50 steel
Spindle Speed at 2000 RPM	2,842 RPM
Blade Tip Speed(ft./min)	18,000
Number of Blades	3
Blade Length(in)	21
Blade Width(in)	2-1/2
Blade Thickness(in)	1/4
Shipping Weight of Base 60" Deck(lbs)	450

Snow Blower	LS3150
Tractor Application	XJ 2000 Series
Overall width(in)	50
Cutting width(in)	49 3/4
Cutting height(in)	20
Impeller drive	Chain #40
Auger drive	Worm gear
Auger diameter(in)	12 3/4
Impeller diameter(in)	15 3/4
Number of blades on impeller	3
Chute rotation	Manual
Adjustable heavy skid shoes	Yes



LS Tractor USA