



**DELIVERY & FINANCING AVAILABLE**

**1845 NORTH COLLEGE FORT COLLINS, CO**  
**TOLL FREE: 877-636-0500**  
[www.LEGACYTRACTORS.COM](http://www.LEGACYTRACTORS.COM)

**Specifications**

CATEGORY	XR4140	XR4140C	XR4145	XR4145C	XR4150	XR4150C	XR4155	XR4155C
	XR4140H	XR4140HC	XR4145H	XR4145HC	XR4150H	XR4150HC	XR4155H	XR4155HC
<b>ENGINE</b>								
Type	3Cyl. In-line Vertical, Water-cooled 4cycle Turbo Diesel, CRDI							
Model(Tier4)	L3C19-T							
Engine HP(Gross)	40		45		50		55	
PTO HP	34.4		38.7		43.0		47.3	
	32.0		36.0		40.0		44.0	
Rated speed, rpm	2,600							
Displacement-cu, in <sup>3</sup> .	114.7							
Fuel tank capacity, gal	12.4 (CABIN) / 10.6 (ROPS)							
Alternator(V-A)	12- 70							
<b>DRIVE TRAIN</b>								
Transmission	Synchro shuttle / HST							
No. of Speed	F16 x R16 (GEAR) / 3 Ranges (HST)							
Brakes	Wet, Multi - disc							
Steering	Hydrostatic Power Steering							
<b>PTO</b>								
Type	Independent							
Rear, rpm	540							
Mid PTO(Option)	2,000							
<b>HYDRAULIC SYSTEM</b>								
Control system	Position / Draft							
Main pump, gpm	8.2							
Steering pump, gpm	4.1 (GEAR) / 5.5 (HST)							
Total flow, gpm	12.3 (GEAR) / 13.7 (HST)							
Category, 3pt hitch	CAT I				CAT II			
Hitch Lift capacity, lbs(Hitch end)	2,755							
Remote valves	2 pairs							
<b>DIMENSION</b>								
Overall length, Bumper to link in.	133							
Overall width with tires, in.	62.5							
Wheelbase, in.	73.2							
Ht to top of rops, in.	93	92	93	92	93	92	93	92
<b>TIRE SIZE</b>								
Ag Front / Rear	9.5 - 16 / 13.6 - 24							
IND Front / Rear	12 - 16.5, 17.5L - 24							
Turf Front / Rear	28x8.5 - 15 / 41 x14 - 20							
<b>WEIGHT</b>								
Total weight without ballast, lbs.	3,869	4,380	3,869	4,380	3,869	4,380	3,869	4,380
	3,935	4,446	3,935	4,446	3,935	4,446	3,935	4,446

Note Specifications and design are subject to change without prior notice.

**Get More Standard Features**

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote control vales (2 pairs)
- Hydrostatic power steering
- Front loader valve and joystick
- Hydraulic draft and position control
- Adjustable seat
- Extendable lower links and telescopic stabilizers
- Drawbar
- Turn signals
- Safety flashers

<b>Front end Loader</b>		LL4104
<b>Tractor Application</b>	XR4100 Series	
Bucker Size, in.	72	
Maximum Lift height, in.	96,3	
Clearance with Attachment Dump, in.	63	
Reach at Maximum Height, in.	9.0	
Maximum Dump Angle, deg.	65	
Maximum Rollback Angle, deg.	34	
Digging Depth, in.	4.3	
Overall Height in Carry Position, in.	49,2	
Lift Capacity(@ Pivot pin), lbs.	2,713	
Breakout Force(@ Pivot pin), lbs.	3,802	

<b>Backhoe</b>		LB2105
<b>Tractor Application</b>	XR4100 Series	
Digging Depth, in.	89,8	
Reach from centerline of swing Pivot, in	125,2	
Loading Height, in.	72,4	
Swing Arc, deg.	180	
Transport Height, in.	83,5	
Bucket Rotating, deg.	180	
Stabilizer Spread(Down position), in.	68,7	
Stabilizer Spread(Up position), in.	46,5	
Bucket Digging force, lbs.	2,673	

**Additional Equipment on Cab Models**

- Deluxe cabin with Heating and A/C
- Cabin air recirculation
- Interior lighting

**Dealer Installed Options**

- Mid PTO
- Beacon lamp kit
- Deluxe stereo system with CD Player, USB
- Room mirror
- Rear wiper
- Sun screen



**LS Tractor USA** | 6900 Corporation Parkway, Battleboro, NC  
P: 252.984.0700 | F: 252.984.0701 | [www.lstractorusa.com](http://www.lstractorusa.com)