



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO
TOLL FREE: 877-636-0500
www.LEGACYTRACTORS.COM

Specifications

CATEGORY	XU5055	XU5055C	XU5065PS	XU5065CPS
ENGINE				
Type	4 Cylinder CRDI, Water-cooled, Turbo			
Model(Tier4)	ISM N4LDI-TA			
Engine HP(Gross)	55		65	
PTO HP	46.5		53.4	
Rated speed, RPM	2,600			
Displacement-cu, in ³ .	135.2			
Fuel tank capacity(gal)	15.8			
Alternator(V-A)	12 - 55			
DRIVE TRAIN				
Transmission	Synchro Shuttle		Power Shuttle	
No. of Speed	16F x 16R			
Brakes	Wet, Multi - disc			
Steering	Hydrostatic Power Steering			
PTO				
Type	Independent			
Rear(rpm)	540			
Mid PTO(Option)	N/A			
HYDRAULIC SYSTEM				
Control system	Position / Draft			
Implement pump, gpm	10.5			
Steering pump, gpm	5.3			
Total flow, gpm	15.8			
Category, 3pt hitch	CAT2			
Hitch Lift capacity, lbs(Hitch end)	4,079			
Remote valves	4 (front), 4 (rear)			
DIMENSION				
Overall length, Bumper to link in.	141.5			
Overall width with tires, in.	67			
Wheelbase, in.	80.3			
Ht to top of rops, in.	102.9	100.7	102.9	100.7
TIRE SIZE				
Ag Front / Rear	9.5 - 20 / 16.9 - 24			
IND Front / Rear	10.5 / 80 - 18, 19.5L - 24			
Turf Front / Rear	36x13.5 - 15, 16.9 - 24			
WEIGHT				
Total weight without ballast, lbs.	4,674	5,121	4,674	5,121

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote control vales (2 pair)
- Hydrostatic power & tilt steering
- Front loader valve and joystick
- Hydraulic draft and position control
- Automatic lift
- Adjustable seat
- Extendable lower links and telescopic stabilizers
- Drawbar
- Turn signals
- Safety flashers
- Standard 7 pin implement socket

Front end Loader	LL5103
Tractor Application	XU-5000 Series
Maximum Lift height, in.	116
Clearance with Attachment Dump, in.	82.5
Reach at Maximum Height, in.	15.1
Maximum Dump Angle, deg.	48
Maximum Rollback Angle, deg.	46
Digging Depth, in.	4.3
Overall Height in Carry Position, in.	65.5
Lift Capacity(@ Pivot pin), lbs.	3,060
Breakout Force(@ Pivot pin), lbs.	4,616
Approx. Weight (Loader w/o Bucket), lbs.	1,276

Backhoe	LB3101
Tractor Application	XU-5000 Series
Digging Depth, in.	94.4
Reach from centerline of swing Pivot, in	136.1
Loading Height, in.	80.3
Swing Arc, deg.	180
Transport Height, in.	92.9
Bucket Rotating, deg.	180
Stabilizer Spread(Down position), in.	68.7
Stabilizer Spread(Up position), in.	46.4
Bucket Digging force, lbs.	3,748

Additional Equipment on Cab Models

- Deluxe cabin with Heating and A/C
- Cabin air recirculation
- Front & Rear windshield washer/wiper system
- Deluxe Stereo system with CD Player, USB

Dealer Installed Options

- Auxiliary fuel tank (additional 5.3 gal.)
- Beacon Lamp Kit



LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC
 P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com