



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO  
**TOLL FREE: 877-636-0500**  
 www.LEGACYTRACTORS.COM

**TYM** | **T354 & T354 CAB (HST)**

WWW.TYM-TRACTORS.COM

MODEL	T354	T354 CAB (HST)	
<b>ENGINE</b>	Engine Manufacturer	Yanmar	Yanmar
	Engine Model	3TNV88C-KKTF	3TNV88C-KKTF
	Engine Type	Natural Aspiration	Natural Aspiration
	Engine HP-Gross	34.2 (25.5)	34.2 (25.5)
	PTO HP (kw)	28.1 (20.9)	26.8 (20.0)
	Rated Engine Speed	2800	2800
	Number of Cylinders	3	3
	Displacement-cu.in. (cc)	100.2 (1642)	100.2 (1642)
	Air Cleaner	Dual Dry	Dual Dry
	Alternator	12V.55A	12V.55A
Fuel System Type	CRDI	CRDI	
<b>POWERTRAIN</b>	Transmission Type	Sync/Shuttle	HST
	Number of Speeds	12/F 12/R	Infinite/3 Range
	Max Traveling Speed, mph(km/h)	13.4 (21.6)	16.1(26)
	Brakes	Wet Disc	Wet Disc
	Steering	Hydrostatic	Hydrostatic
	Clutch	Dry Single Plate	N/A
<b>HYDRAULIC SYSTEM</b>	Pump Type	Dual Gear Pump	Dual Gear Pump
	Implement Pump Cap.gpm(L/Min)	6.3 (23.9)	6.3 (23.9)
	Steering Pump Cap. gpm (L/Min)	4.3 (16.2)	4.6 (17.3)
	Max Total Flow gpm (L/Min)	10.6 (40.1)	10.9 (41.2)
	Category, 3 Point Hitch	1	1
	Hitch lift Capacity, lb. (kg)	2646 (1200)	2646 (1200)
	At 24 inches behind link ends, lb(kg)	1764 (800)	1764 (800)
	Lift Control Type	Position	Position
	Joy Stick Valve	Standard	Standard
No. of Standard Remote Valves-Option	1	1	
<b>PTO</b>	PTO Type	Independent	Independent
	PTO Control	Electric/Hydro	Electric/Hydro
	PTO Mid (rpm)-Option	N/A	2000
	PTO Rear (rpm)	540/1000	540/1000
	PTO Shaft Diameter in. (mm)	1 3/8 (35)	1 3/8 (35)
<b>CAPACITIES</b>	Fuel Tank, U.S. gal. (L)	9.0 (34)	9.0 (34)
	Cooling System U.S. qt. (L)	5 (4.8)	5 (4.8)
	Crankcase (witd filter) U.S. qt. (L)	4.2 (4)	4.2 (4)
	Trans & Hydr. System, U.S. gal. (L)	8.5 (32)	9.25 (35)
	Front Axle qt. (L)	8.7 (8.2)	8.7 (8.2)
<b>DIMENSIONS</b>	Overall Length, in. (mm) with 3P	126 (3200)	130.5 (3315)
	Overall Width, in. (mm)	53.5 (1360)	52 (1320)
	Wheelbase, in. (mm)	64.5 (1640)	66.1 (1680)
	Height to Top of ROPS, in. (mm)	94.5 (2400)	94.4 (2400)
	Min. Ground Clearence, in. (mm)	12.8 (325)	13.8 (350)
	Min. Turn Radius, in (mm) with Brakes	94.4 (2400)	94.4 (2400)
	Min. Turn Radius, in (mm) w/o brakes	116 (2950)	116 (2950)
<b>STANDARD TIRES</b>	Agricultural Front	7x6-16	7x6-16
	Agricultural Rear	11.2x24-4	11.2-24x4
	Industrial Front	10x16.5-6	10x16.5-6
	Industrial Rear	43x16x20-4	43x16x20-4
<b>ROPS &amp; WEIGHT</b>	Roll Over Protection Standard	ROPS	ROPS
	Total Weight, lb (kg)	3065 (1390)	3108 (1410)

