



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO  
**TOLL FREE: 877-636-0500**  
 www.LEGACYTRACTORS.COM

# TYM | T454 & T454 CAB

WWW.TYM-TRACTORS.COM

MODEL	T454	T454 CAB	
<b>ENGINE</b>	Engine Manufacturer	Yanmar	Yanmar
	Engine Model	4TNV88C-KKTF	4TNV88C-KKTF
	Engine Type	Natural Aspiration	Natural Aspiration
	Engine HP-Gross	46 (34.3)	46 (34.3)
	PTO HP (kw)	36.7 (27.4)	34.2 (25.5)
	Rated Engine Speed	2800	2800
	Number of Cylinders	4	4
	Displacement-cu.in. (cc)	133.6(2190)	133.6 (2190)
	Air Cleaner	Dual Dry	Dual Dry
	Alternator	12V.55A	12V.55A
Fuel System Type	CRDI	CRDI	
<b>POWERTRAIN</b>	Transmission Type	Sync/Shuttle	HST
	Number of Speeds	16/F 16/R	Infinite/3 Range
	Max Traveling Speed, mph(km/h)	19.9 (32.0)	19.9 (32.0)
	Brakes	Wet Disc	Wet Disc
	Steering	Hydrostatic	Hydrostatic
	Clutch	Dry Single Plate	N/A
<b>HYDRAULIC SYSTEM</b>	Pump Type	Dual Gear Pump	Dual Gear Pump
	Implement Pump Cap.gpm(L/Min)	8.8 (33.5)	8.8 (33.5)
	Steering Pump Cap. gpm (L/Min)	4.6 (17.6)	4.6 (17.6)
	Max Total Flow gpm (L/Min)	13.4 (51.1)	13.4 (51.1)
	Category, 3 Point Hitch	1	1
	Hitch lift Capacity, lb. (kg)	3314 (1503)	3314 (1503)
	At 24 inches behind link ends, lb(kg)	2945 (1336)	2945 (1336)
	Lift Control Type	Position/Draft	Position/Draft
	Joy Stick Valve	Standard	Standard
No. of Standard Remote Valves-Option	2	2	
<b>PTO</b>	PTO Type	Independent	Independent
	PTO Control	Electric/Hydro	Electric/Hydro
	PTO Mid (rpm)-Option	N/A	N/A
	PTO Rear (rpm)	540	540
	PTO Shaft Diameter in. (mm)	1 3/8 (35)	1 3/8 (35)
<b>CAPACITIES</b>	Fuel Tank, U.S. gal. (L)	15.85 (60)	15.85 (60)
	Cooling System U.S. qt. (L)	9.8 (9.3)	9.8 (9.3)
	Crankcase (witd filter) U.S. qt. (L)	5.6 (5.3)	5.6 (5.3)
	Trans & Hydr. System, U.S. gal. (L)	9.2 (35)	9.2 (35)
	Front Axle qt. (L)	10.5 (10)	10.5 (10)
<b>DIMENSIONS</b>	Overall Length, in. (mm) with 3P	141.3 (3590)	141.3 (3590)
	Overall Width, in. (mm)	63.8 (1620)	63.8 (1620)
	Wheelbase, in. (mm)	76.2 (1935)	76.2 (1935)
	Height to Top of ROPS, in. (mm)	102.1 (2594)	99.6 (2530)
	Min. Ground Clearence, in. (mm)	13.8 (350)	13.8 (350)
	Min. Turn Radius, in (mm) with Brakes	131.9 (3352)	131.9 (3352)
	Min. Turn Radius, in (mm) w/o brakes	150.4 (3820)	150.4 (3820)
<b>STANDARD TIRES</b>	Agricultural Front	9.5x16-6	9.5x16-6
	Agricultural Rear	13.6-26	13.6-26
	Industrial Front	12x16.5-6	12x16.5-6
	Industrial Rear	16.9x24-8	16.9x24-8
<b>ROPS &amp; WEIGHT</b>	Roll Over Protection Standard	ROPS	ROPS
	Total Weight, lb (kg)	3814 (1730)	4078 (1850)

