



DELIVERY & FINANCING AVAILABLE

1845 NORTH COLLEGE FORT COLLINS, CO
TOLL FREE: 877-636-0500
www.LEGACYTRACTORS.COM

TYM | T1054 SP

| | | T1054 SP |
|--------------------------|---------------------------------------|------------------------------|
| ENGINE | Engine Manufacturer | DOOSAN INFRACORE |
| | Engine Model | DL03-LEA04 |
| | Engine Type | Turbo |
| | Engine HP-Gross | 105 (78.3) |
| | PTO HP (kw) | 95.5 (70.2) |
| | Rated Engine Speed | 2300 |
| | Number of Cylinders | 4 |
| | Displacement-cu.in. (cc) | 208 (3409) |
| | Air Cleaner | Dual Dry |
| | Alternator | 12V, 110A |
| Fuel System Type | CRDI | |
| POWERTRAIN | Transmission Type | Power Shuttle & Hi/Lo shift |
| | Number of Speeds | 32F / 32R |
| | Max Traveling Speed, mph(km/h) | 24.9 (40) |
| | Brakes | Wet Disc |
| | Steering | Hydrostatic |
| HYDRAULIC SYSTEM | Clutch | Wet Multi Plate |
| | Pump Type | Dual Gear Pump |
| | Implement Pump Cap.gpm(L/Min) | 15.6 (59) |
| | Steering Pump Cap. gpm (L/Min) | 7.1 (26.7) |
| | Max Total Flow gpm (L/Min) | 22.7 (85.7) |
| | Category, 3 Point Hitch | II |
| | Hitch lift Capacity, lb. (kg) | 6860 (3110), 4340 (9570) Opt |
| | At 24 inches behind link ends, lb(kg) | 5490 (2490), 6490 (2944) Opt |
| | Lift Control Type | Pos/Draft/Elec |
| Joy Stick Valve | Standard | |
| PTO | No. of Standard Remote Valves-Option | 3 |
| | PTO Type | Independent |
| | PTO Control | Electric/Hydro |
| | PTO Mid (rpm)-Option | N/A |
| | PTO Rear (rpm) | 540/750/1000 |
| CAPACITIES | PTO Shaft Diameter in. (mm) | 1 3/8 (35) |
| | Fuel Tank, U.S. gal. (L) | 29.1 (110)+DEF 5.3 (20) |
| | Cooling System U.S. qt. (L) | - |
| | Crankcase (witd filter) U.S. qt. (L) | 4.22 (16) |
| | Trans & Hydr. System, U.S. gal. (L) | 19.8 (75) |
| DIMENSIONS | Front Axle qt. (L) | 18.5 (17) |
| | Overall Length, in. (mm) with 3P | 165.4 (4200) |
| | Overall Width, in. (mm) | 86 (2185) |
| | Wheelbase, in. (mm) | 90.55 (2300) |
| | Height to Top of ROPS, in. (mm) | 107 (2718) |
| | Min. Ground Clearance, in. (mm) | 18.3 (465) |
| | Min. Turn Radius, in (mm) with Brakes | 143.7 (3650) |
| STANDARD TIRES | Min. Turn Radius, in (mm) w/o brakes | 162 (4120) |
| | Agricultural Front | 14.9x24-6 |
| | Agricultural Rear | 18.4x34-6 |
| | Industrial Front | - |
| ROPS & WEIGHT | Industrial Rear | - |
| | Roll Over Protection Standard | CAB with AC |
| | Total Weight, lb (kg) | 8666 (3930) |

